

Data Sheet

page 1 of 3

UV SMD LED

EOLS-325-695

Rev. 03, 2020

Radiation	Type	Case
UVA	AlGaIn	Ceramic SMD 3535 (1414), flat top

Unit: mm

Applications:

- Analytical instruments: biochemical, medical, and scientific analysis
- Photo catalyst
- Medical phototherapy
- UV curing: spot bonding, printing, film coating and general purpose

Maximum Ratings

$T_{amb} = 25^{\circ}\text{C}$, unless otherwise specified

Parameter	Test conditions	Symbol	Value	Unit
Forward current		I_F	150	mA
Junction temperature		T_J	90	$^{\circ}\text{C}$
Operating temperature range		T_{amb}	-30 to +85	$^{\circ}\text{C}$
Storage temperature range	no condensation	T_{stg}	-40 to +85	$^{\circ}\text{C}$
Thermal resistance junction-ambient		R_{th}	20	K/W

Optical and Electrical Characteristics

$T_{amb} = 25^{\circ}\text{C}$, unless otherwise specified

Parameter	Symbol	Conditions	Min	typ	max	Unit
Forward voltage	V_F	$I_F = 100 \text{ mA}$		4.7		V
Radiant power	Φ_e	$I_F = 100 \text{ mA}$	7	12	18	mW
Peak wavelength	λ_p	$I_F = 100 \text{ mA}$	320	325	330	nm
FWHM	$\Delta\lambda_{0.5}$	$I_F = 100 \text{ mA}$		13		nm
Viewing half angle	φ	$I_F = 100 \text{ mA}$		120		deg



We reserve the right to make changes to improve technical design and may do so without further notice. Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer.

EPIGAP Optronik GmbH


Koepenicker Str. 325
D-12555 Berlin
Fon: +49 (0)30 657637 60
Fax: +49 (0)30 657637 70
sales@epigap-optronic.de

Data Sheet


UV SMD LED

EOLS-325-695


page 2 of 3
Rev. 03, 2020




Spectrum at 100 mA




Radiation pattern



Forward current vs forward voltage




Radiant power vs forward current



Unit : mm

Recommended solder pad



Recommended reflow soldering profile



We reserve the right to make changes to improve technical design and may do so without further notice. Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer.

EPIGAP Optronik GmbH

Koepenicker Str. 325
D-12555 Berlin
Fon: +49 (0)30 657637 60
Fax: +49 (0)30 657637 70
sales@epigap-optronic.de

EQ Photonics GmbH
Zeppelinstr. 4
DEU - 85399 Hallbergmoos
Tel: +49-811-998 707-0
Fax: +49-811-998 707-49
Mail: info@eqphotonics.de
Web: www.eqphotonics.de




Data Sheet

UV SMD LED

EOLS-325-695

page 3 of 3
Rev. 03, 2020



Derating curve

Art. No. 133 202



We reserve the right to make changes to improve technical design and may do so without further notice. Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer.